



Stain Proof Premium Impregnating Sealer (Stain Proof Original)

ICP Building Solutions Group (CAN)

Version No: 4.7

Safety Data Sheet according to WHMIS 2015 requirements

Issue Date: 04/01/2020

Print Date: 04/01/2020

S.GHS.CAN.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Stain Proof Premium Impregnating Sealer (Stain Proof Original)
Synonyms	Not Available
Proper shipping name	FLAMMABLE LIQUID, N.O.S. (contains ethanol)
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Water and stain protection for masonry substrates- sealer
--------------------------	---

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Building Solutions Group (CAN)
Address	555 Bay St. North Hamilton, Ontario L8L 1H1 Canada
Telephone	978-623-9980
Fax	Not Available
Website	www.icpgroup.com
Email	Not Available

Emergency phone number

Association / Organisation	Chemtel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Eye Irritation Category 2A, Acute Aquatic Hazard Category 3, Flammable Liquid Category 2, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 2, Reproductive Toxicity Category 1B, Germ cell mutagenicity Category 2, Specific target organ toxicity - repeated exposure Category 1, Chronic Aquatic Hazard Category 3
----------------	--

Label elements

Hazard pictogram(s)	
---------------------	--

SIGNAL WORD	DANGER
-------------	--------

Hazard statement(s)

H319	Causes serious eye irritation.
H225	Highly flammable liquid and vapour.
H332	Harmful if inhaled.

Continued...

Stain Proof Premium Impregnating Sealer (Stain Proof Original)

H315	Causes skin irritation.
H360	May damage fertility or the unborn child.
H341	Suspected of causing genetic defects.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Physical and Health hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Precautionary statement(s) Prevention

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/attention.
P305+P351+P313	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue Rinsing.
P305+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P302+P352	IF ON SKIN: Wash with plenty of water
P362	Take off contaminated clothing and wash before reuse.

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
-------------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64-17-5	50-60	<u>ethanol</u>
77-58-7	1-5	<u>dibutyltin dilaurate</u>
Not Available	3-7	<u>Poly(Hexadecyl Acrylate/2-Hydroxyethyl Methacrylate/Octadecyl Acrylate/3,3,4,4,5,5,6,6,7,7,8,8,8-Tridecafluorooctyl Methacrylate) 1793072-86-2</u>
123-86-4	1-5	<u>n-butyl acetate</u>
2943-75-1	1-5	<u>octyltriethoxysilane</u>
17980-47-1	35-45	<u>isobutyltriethoxysilane</u>

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.

Continued...

Stain Proof Premium Impregnating Sealer (Stain Proof Original)

Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short term repeated exposures to ethanol:

- ▶ Acute ingestion in non-tolerant patients usually responds to supportive care with special attention to prevention of aspiration, replacement of fluid and correction of nutritional deficiencies (magnesium, thiamine pyridoxine, Vitamins C and K).
- ▶ Give 50% dextrose (50-100 ml) IV to obtunded patients following blood draw for glucose determination.
- ▶ Comatose patients should be treated with initial attention to airway, breathing, circulation and drugs of immediate importance (glucose, thiamine).
- ▶ Decontamination is probably unnecessary more than 1 hour after a single observed ingestion. Cathartics and charcoal may be given but are probably not effective in single ingestions.
- ▶ Fructose administration is contra-indicated due to side effects.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Special protective equipment and precautions for fire-fighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Liquid and vapour are highly flammable. ▶ Severe fire hazard when exposed to heat, flame and/or oxidisers. Combustion products include: <ul style="list-style-type: none"> , carbon dioxide (CO₂) , silicon dioxide (SiO₂) , other pyrolysis products typical of burning organic material.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> ▶ Remove all ignition sources. ▶ Clean up all spills immediately.
Major Spills	<ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ Containers, even those that have been emptied, may contain explosive vapours. ▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers. ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs.
Other information	<ul style="list-style-type: none"> ▶ Store in original containers in approved flame-proof area. ▶ No smoking, naked lights, heat or ignition sources.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Packing as supplied by manufacturer. ▶ Plastic containers may only be used if approved for flammable liquid. ▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
---------------------------	--

Stain Proof Premium Impregnating Sealer (Stain Proof Original)

Storage incompatibility

- ▶ Avoid oxidising agents, acids, acid chlorides, acid anhydrides, chloroformates.
- ▶ Segregate from alcohol, water.
- ▶ Avoid strong acids, bases.

*

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	ethanol	Ethyl alcohol (Ethanol)	1,000 ppm / 1,900 mg/m ³	1,900 mg/m ³ / 1,000 ppm	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	ethanol	Ethanol	Not Available	1000 ppm	Not Available	TLV Basis: upper respiratory tract irritation
Canada - Alberta Occupational Exposure Limits	ethanol	Ethanol (Ethyl alcohol)	1000 ppm / 1880 mg/m ³	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	ethanol	Ethanol	1000 ppm	1250 ppm	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	ethanol	Not Available	Not Available	1000 ppm	Not Available	TLV® Basis: URT irr
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	ethanol	Ethyl alcohol	1000 ppm / 1880 mg/m ³	Not Available	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	ethanol	Ethanol	1000 ppm	1250 ppm	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	ethanol	Ethanol	Not Available	1000 ppm	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	ethanol	Ethanol	Not Available	1000 ppm	Not Available	TLV® Basis: URT irr
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	dibutyltin dilaurate	Tin, organic compounds (as Sn) - Skin	0.1 mg/m ³	0.2 mg/m ³	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	dibutyltin dilaurate	Tin - Organic compounds (as Sn)	0.1 mg/m ³	0.2 mg/m ³	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	dibutyltin dilaurate	Tin, as Sn: Organic compounds	0.1 mg/m ³	0.2 mg/m ³	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	dibutyltin dilaurate	Tin, (as Sn): organic compounds	0.1 mg/m ³	0.2 mg/m ³	Not Available	Skin
Canada - Manitoba Occupational Exposure Limits	dibutyltin dilaurate	Not Available	0.1 mg/m ³	0.2 mg/m ³	Not Available	TLV® Basis: Eye & URT irr; headache; nausea; CNS & immune eff
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	dibutyltin dilaurate	Tin: Organic compounds (as Sn)	0.1 mg/m ³	0.2 mg/m ³	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	dibutyltin dilaurate	Tin, (as Sn): organic compounds	0.1 mg/m ³	0.2 mg/m ³	Not Available	Skin
Canada - Northwest Territories Occupational Exposure Limits (English)	dibutyltin dilaurate	Tin, (as Sn): oxide and inorganic compounds except SnH ₄	2 mg/m ³	4 mg/m ³	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	dibutyltin dilaurate	Tin - Organic compounds, as Sn	0.1 mg/m ³	0.2 mg/m ³	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	dibutyltin dilaurate	Tin, organic compounds, as Sn	0.1 mg/m ³	0.2 mg/m ³	Not Available	TLV® Basis: Eye & URT irr; headache; nausea; CNS & immune eff
Canada - Ontario Occupational Exposure Limits	dibutyltin dilaurate	Tin, as Sn - Organic compounds, as Sn	0.1 mg/m ³	Not Available	Not Available	Skin (organic compounds)
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	n-butyl acetate	n-Butyl acetate	150 ppm / 710 mg/m ³	950 mg/m ³ / 200 ppm	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	n-butyl acetate	n-Butyl acetate	150 ppm	200 ppm	Not Available	TLV Basis: eye & upper respiratory tract irritation
Canada - Alberta Occupational Exposure Limits	n-butyl acetate	n-Butyl acetate	150 ppm / 713 mg/m ³	950 mg/m ³ / 200 ppm	Not Available	Not Available

Continued...

Stain Proof Premium Impregnating Sealer (Stain Proof Original)

Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	n-butyl acetate	n-Butyl acetate	150 ppm	200 ppm	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	n-butyl acetate	Not Available	150 ppm	200 ppm	Not Available	TLV® Basis: Eye & URT irr
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	n-butyl acetate	n-Butyl acetate	150 ppm / 713 mg/m3	950 mg/m3 / 200 ppm	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	n-butyl acetate	n-Butyl acetate	150 ppm	200 ppm	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	n-butyl acetate	n-Butyl acetate	20 ppm	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	n-butyl acetate	Butyl acetate, all isomers	50 ppm	150 ppm	Not Available	TLV® Basis: Eye & URT irr

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ethanol	Ethanol: (Ethyl alcohol)	Not Available	Not Available	15000* ppm
dibutyltin dilaurate	Dibutyltin dilaurate; (Dibutylbis(lauroyloxy)stannane)	1.1 mg/m3	8 mg/m3	48 mg/m3
n-butyl acetate	Butyl acetate, n-	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
ethanol	3,300 ppm	Not Available
dibutyltin dilaurate	25 mg/m3	Not Available
Poly(Hexadecyl Acrylate/2-Hydroxyethyl Methacrylate/Octadecyl Acrylate/3,3,4,4,5,5,6,6,7,7,8,8,8-Tridecafluorooctyl Methacrylate) 1793072-86-2	Not Available	Not Available
n-butyl acetate	1,700 ppm	Not Available
octyltriethoxysilane	Not Available	Not Available
isobutyltriethoxysilane	Not Available	Not Available


OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
octyltriethoxysilane	E	≤ 0.1 ppm
isobutyltriethoxysilane	E	≤ 0.1 ppm

Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▶ Overalls. ▶ PVC Apron. ▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. ▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available

Stain Proof Premium Impregnating Sealer (Stain Proof Original)

Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	-10.56	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Partly miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	<p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of vapours, fumes or aerosols, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Animal testing shows that the most common signs of inhalation overdose is inco-ordination and drowsiness. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p>						
Ingestion	<p>The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum. Ingestion of ethanol (ethyl alcohol, "alcohol") may produce nausea, vomiting, bleeding from the digestive tract, abdominal pain, and diarrhoea. Effects on the body:</p> <table border="1"> <thead> <tr> <th>Blood concentration</th> <th>Effects</th> </tr> </thead> <tbody> <tr> <td><1.5 g/L</td> <td>Mild: impaired vision, co-ordination and reaction time; emotional instability</td> </tr> <tr> <td>1.5-3.0 g/L</td> <td>Moderate: Slurred speech, confusion, inco-ordination, emotional instability, disturbances in perception and senses, possible blackouts, and impaired objective performance in standardized tests.</td> </tr> </tbody> </table> <p>Accidental ingestion of the material may be damaging to the health of the individual.</p>	Blood concentration	Effects	<1.5 g/L	Mild: impaired vision, co-ordination and reaction time; emotional instability	1.5-3.0 g/L	Moderate: Slurred speech, confusion, inco-ordination, emotional instability, disturbances in perception and senses, possible blackouts, and impaired objective performance in standardized tests.
Blood concentration	Effects						
<1.5 g/L	Mild: impaired vision, co-ordination and reaction time; emotional instability						
1.5-3.0 g/L	Moderate: Slurred speech, confusion, inco-ordination, emotional instability, disturbances in perception and senses, possible blackouts, and impaired objective performance in standardized tests.						
Skin Contact	<p>The material may accentuate any pre-existing dermatitis condition. Open cuts, abraded or irritated skin should not be exposed to this material. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</p>						
Eye	<p>Direct contact of the eye with ethanol (alcohol) may cause an immediate stinging and burning sensation, with reflex closure of the lid, and a temporary, tearing injury to the cornea together with redness of the conjunctiva. Discomfort may last 2 days but usually the injury heals without treatment. There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.</p>						
Chronic	<p>Based on experiments and other information, there is ample evidence to presume that exposure to this material can cause genetic defects that can be inherited. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.</p>						

Continued...

Stain Proof Premium Impregnating Sealer (Stain Proof Original)

Prolonged exposure to ethanol may cause damage to the liver and cause scarring. It may also worsen damage caused by other agents.

Stain Proof Premium Impregnating Sealer (Stain Proof Original)	TOXICITY	IRRITATION
		Not Available
ethanol	TOXICITY	IRRITATION
	Inhalation (rat) LC50: 124.7 mg/l/4H ^[2]	Eye (rabbit): 500 mg SEVERE
	Oral (rat) LD50: =1501 mg/kg ^[2]	Eye (rabbit):100mg/24hr-moderate
		Eye: adverse effect observed (irritating) ^[1]
		Skin (rabbit):20 mg/24hr-moderate
		Skin (rabbit):400 mg (open)-mild
		Skin: no adverse effect observed (not irritating) ^[1]
dibutyltin dilaurate	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 100 mg/24h -moderate
	Inhalation (mouse) LC50: 0.075 mg/l/2H ^[2]	Skin (rabbit): 500 mg/24h - mild
	Oral (rat) LD50: 175 mg/kg ^[2]	
Poly(Hexadecyl Acrylate/2-Hydroxyethyl Methacrylate/Octadecyl Acrylate/3,3,4,4,5,5,6,6,7,7,8,8,8-Tridecafluorooctyl Methacrylate) 1793072-86-2	TOXICITY	IRRITATION
	Not Available	Not Available
n-butyl acetate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 3200 mg/kg ^[2]	Eye (human): 300 mg
	Inhalation (rat) LC50: 1.802 mg/l/4 h ^[1]	Eye (rabbit): 20 mg (open)-SEVERE
	Oral (rat) LD50: =10700 mg/kg ^[2]	Eye (rabbit): 20 mg/24h - moderate
		Eye: no adverse effect observed (not irritating) ^[1]
		Skin (rabbit): 500 mg/24h-moderate
		Skin: no adverse effect observed (not irritating) ^[1]
octyltriethoxysilane	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 5177.16 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (rat) LD50: >=5110 mg/kg ^[1]	Skin: adverse effect observed (irritating) ^[1]
isobutyltriethoxysilane	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Not Available
	Inhalation (rat) LC50: 5.88 mg/l/4h ^[2]	
	Oral (rat) LD50: >5000 mg/kg ^[2]	

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

DIBUTYLTIN DILAURATE	Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation.
N-BUTYL ACETATE	Generally,linear and branched-chain alkyl esters are hydrolysed to their component alcohols and carboxylic acids in the intestinal tract, blood and most tissues throughout the body. Following hydrolysis the component alcohols and carboxylic acids are metabolized Oral acute toxicity studies have been reported for 51 of the 67 esters of aliphatic acyclic primary alcohols and aliphatic linear saturated carboxylic acids. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
OCTYLTRIEHOXYSILANE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. No significant acute toxicological data identified in literature search.
Stain Proof Premium Impregnating Sealer (Stain Proof Original) & OCTYLTRIEHOXYSILANE	Low molecular weight alkoxysilane can cause irreversible lung damage when inhaled at low dose. It is not an obvious skin irritant.
ETHANOL & N-BUTYL ACETATE	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Acute Toxicity	✓	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗

Stain Proof Premium Impregnating Sealer (Stain Proof Original)

Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✓
Mutagenicity	✓	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Stain Proof Premium Impregnating Sealer (Stain Proof Original)	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
		Not Available	Not Available	Not Available	Not Available
ethanol	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	11-mg/L	2
	EC50	48	Crustacea	2mg/L	4
	EC50	96	Algae or other aquatic plants	17.921mg/L	4
	NOEC	2016	Fish	0.000375mg/L	4
dibutyltin dilaurate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	EC50	48	Crustacea	<0.463mg/L	2
	EC50	72	Algae or other aquatic plants	>1mg/L	2
	NOEC	48	Crustacea	1.7mg/L	2
Poly(Hexadecyl Acrylate/2-Hydroxyethyl Methacrylate/Octadecyl Acrylate/3,3,4,4,5,5,6,6,7,7,8,8,8-Tridecafluorooctyl Methacrylate) 1793072-86-2	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
n-butyl acetate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	18mg/L	4
	EC50	48	Crustacea	=32mg/L	1
	EC50	96	Algae or other aquatic plants	1.675mg/L	3
	EC90	72	Algae or other aquatic plants	1-540.7mg/L	2
	NOEC	504	Crustacea	23.2mg/L	2
octyltriethoxysilane	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>0.055mg/L	2
	EC50	48	Crustacea	>0.049mg/L	2
	EC50	72	Algae or other aquatic plants	>0.13mg/L	2
	NOEC	48	Crustacea	>=0.049mg/L	2
isobutyltriethoxysilane	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	26.741mg/L	3
	EC50	48	Crustacea	>49.1mg/L	2
	EC50	96	Algae or other aquatic plants	<1.000mg/L	3
	EC10	72	Algae or other aquatic plants	>36mg/L	2
	NOEC	48	Crustacea	35.4mg/L	2

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

For Ethanol:

log Kow: -0.31 to -0.32;

Koc 1: Estimated BCF= 3;

Half-life (hr) air: 144;

Half-life (hr) H2O surface water: 144;

Henry's atm m³/mol: 6.29E-06;

BOD 5 if unstated: 0.93-1.67,63%

COD: 1.99-2.11,97%;

ThOD : 2.1.

Environmental Fate: Terrestrial - Ethanol quickly biodegrades in soil but may leach into ground water; most is lost by evaporation.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Continued...

Stain Proof Premium Impregnating Sealer (Stain Proof Original)

Ingredient	Persistence: Water/Soil	Persistence: Air
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
dibutyltin dilaurate	HIGH	HIGH
n-butyl acetate	LOW	LOW
octyltriethoxysilane	HIGH	HIGH
isobutyltriethoxysilane	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
ethanol	LOW (LogKOW = -0.31)
dibutyltin dilaurate	LOW (BCF = 110)
n-butyl acetate	LOW (BCF = 14)
octyltriethoxysilane	MEDIUM (LogKOW = 4.2394)
isobutyltriethoxysilane	LOW (LogKOW = 2.2015)

Mobility in soil

Ingredient	Mobility
ethanol	HIGH (KOC = 1)
dibutyltin dilaurate	LOW (KOC = 64610000)
n-butyl acetate	LOW (KOC = 20.86)
octyltriethoxysilane	LOW (KOC = 187100)
isobutyltriethoxysilane	LOW (KOC = 13550)


SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible. ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ Recycle wherever possible. ▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
------------------------------	--

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	NO

Land transport (TDG)

UN number	1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (contains ethanol)
Transport hazard class(es)	Class : 3 Subrisk : Not Applicable
Packing group	II
Environmental hazard	Not Applicable
Special precautions for user	Special provisions : 16, 150 Explosive Limit and Limited Quantity Index : 1 L ERAP Index : Not Applicable

Air transport (ICAO-IATA / DGR)

UN number	1993
UN proper shipping name	Flammable liquid, n.o.s. * (contains ethanol)
Transport hazard class(es)	ICAO/IATA Class : 3 ICAO / IATA Subrisk : Not Applicable

Stain Proof Premium Impregnating Sealer (Stain Proof Original)

	ERG Code	3H
Packing group	II	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions	A3
	Cargo Only Packing Instructions	364
	Cargo Only Maximum Qty / Pack	60 L
	Passenger and Cargo Packing Instructions	353
	Passenger and Cargo Maximum Qty / Pack	5 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y341
	Passenger and Cargo Limited Maximum Qty / Pack	1 L

Sea transport (IMDG-Code / GGVSee)

UN number	1993	
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (contains ethanol)	
Transport hazard class(es)	IMDG Class	3
	IMDG Subrisk	Not Applicable
Packing group	II	
Environmental hazard	Not Applicable	
Special precautions for user	EMS Number	F-E , S-E
	Special provisions	274
	Limited Quantities	1 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

ETHANOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

DIBUTYLTIN DILAUATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

POLY(HEXADECYL ACRYLATE/2-HYDROXYETHYL METHACRYLATE/OCTADECYL ACRYLATE/3,3,4,4,5,5,6,6,7,7,8,8,8-TRIDECAFLUOROCTYL METHACRYLATE) 1793072-86-2 IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

N-BUTYL ACETATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

OCTYLTRIETHOXYSILANE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

ISOBUTYLTRIETHOXYSILANE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (n-butyl acetate; ethanol; dibutyltin dilaurate; isobutyltriethoxysilane; octyltriethoxysilane)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes

Continued...

Stain Proof Premium Impregnating Sealer (Stain Proof Original)

Mexico - INSQ	No (isobutyltriethoxysilane; octyltriethoxysilane)
Vietnam - NCI	Yes
Russia - ARIPS	No (isobutyltriethoxysilane)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	04/01/2020
Initial Date	01/24/2020

CONTACT POINT

****PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES****

SDS Version Summary

Version	Issue Date	Sections Updated
3.7.1.1.1	04/01/2020	Ingredients, Physical Properties

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
 PC—STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit.
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

Powered by AuthorTe, from Chemwatch.