

Dry-Treat INTENSIFIA

Dry-Treat

Chemwatch: 4878-19 Version No: 4.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 2

Issue Date: 29/10/2013 Print Date: 19/04/2016 Initial Date: Not Available S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier	
Product name	Dry-Treat INTENSIFIA

Synonyms INTENSIFIA, Intensifier for natural stone, oil and water repellent Other means of Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

identification

Use according to manufacturer's directions. Intensifier for porous stone, tile and concrete.

Details of the supplier of the safety data sheet

Registered company name	Dry-Treat	Dry-Treat Ltd	Dry-Treat
Address	4/149-155 Pascoe Vale Rd. VIC Moonee Ponds 3039 Australia	United Kingdom	150 Dascomb Road MA Andover 01810 United States
Telephone	1800 675 119 (AUS)	0800 0964 760 (UK)	+1 866 667 5119 (USA)
Fax	+61 2 9954 3162	+61 2 9954 3162	+61 2 9954 3162
Website	Not Available	Not Available	Not Available
Email	Not Available	sds@drytreat.com	Not Available

Emergency telephone number

Association / Organisation	Not Available	Not Available	Not Available
Emergency telephone numbers	+1 813 248 0585 (Outside USA)	+1 813 248 0585 (Outside USA)	(800) 255 3924
Other emergency telephone numbers	Not Available	Not Available	+1 813 248 0585 (Outside USA)

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

COMBUSTIBLE LIQUID, regulated for storage purposes only

COMPONITION TO Survive Composition of the storage purposes only	
Poisons Schedule	Not Applicable
Classification [1]	Flammable Liquid Category 4, Acute Aquatic Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements	Not Applicable
SIGNAL WORD	WARNING

Hazard statement(s)

mazara statement(s)	
H227	Combustible liquid
H402	Harmful to aquatic life

Precautionary statement(s) Prevention	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Dry-Treat INTENSIFIA

Issue Date: 29/10/2013
Print Date: 19/04/2016

Precautionary statement(s) Response

P370+P378

In case of fire: Use alcohol resistant foam or normal protein foam for extinction.

Precautionary statement(s) Storage

P403+P235

Store in a well-ventilated place. Keep cool

Precautionary statement(s) Disposal

P501

Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available	100	Ingredients determined not to be hazardous [Manufacturer]

SECTION 4 FIRST AID MEASURES

Description of first aid measures

If this product comes in contact with the eyes:

- ▶ Wash out immediately with fresh running water
- Fasure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin Contact

▶ Immed

- ▶ Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
 Seek medical attention in event of irritation.
- ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.
- Inhalation
- Other measures are usually unnecessary.
- ► Immediately give a glass of water.
- Ingestion
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

If skin contact occurs:

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ► Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- ▶ Prevent, by any means available, spillage from entering drains or water courses.
- ▶ Use water delivered as a fine spray to control fire and cool adjacent area.
- ► High temperature decomposition products include silicon dioxide, small amounts of formaldehyde, formic acid, acetic acid and traces of silicon polymers.
- These gases may ignite and, depending on circumstances, may cause the resin/polymer to ignite.
 An outer skin of silica may also form. Extinguishing of fire, beneath the skin, may be difficult.
- Combustible.

Fire/Explosion Hazard

- Slight fire hazard when exposed to heat or flame.
- ▶ Heating may cause expansion or decomposition leading to violent rupture of containers
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include:carbon dioxide (CO2)nitrogen oxides (NOx)silicon dioxide (SiO2)other pyrolysis products typical of burning organic materialMay emit corrosive fumes. CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills

- Remove all ignition sources.
 - Clean up all spills immediately.

 Avoid breathing vapours and contact with skin and eyes.

Issue Date: 29/10/2013
Print Date: 19/04/2016

- Control personal contact with the substance, by using protective equipment.
 Silicone fluids, even in small quantities, may present a slip hazard.
 It may be necessary to rope off area and place warning signs around perimeter.
 - Clean up area from spill, with suitable absorbant, as soon as practically possible.
 Final cleaning may require use of steam, solvents or detergents.
 - Major Spills Moderate hazard.
 - Clear area of personnel and move upwind.
 - ► Alert Fire Brigade and tell them location and nature of hazard.
 - ▶ Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

- DO NOT allow clothing wet with material to stay in contact with skin
- ► Avoid all personal contact, including inhalation.
- · Wear protective clothing when risk of exposure occurs
- ▶ Use in a well-ventilated area.
- ▶ Prevent concentration in hollows and sumps.

Other information

- ► Store in original containers.
- ► Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- ▶ Store in a cool, dry, well-ventilated area

Conditions for safe storage, including any incompatibilities

Suitable container

- ▶ Metal can or drum
- Packaging as recommended by manufacturer.
- ▶ Check all containers are clearly labelled and free from leaks.

Storage incompatibility

- Avoid strong acids, bases
- ► Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Dry-Treat INTENSIFIA	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Personal protection







Eye and face protection

- ► Safety glasses with side shields.
- Chemical goggles
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

See Hand protection below

- ► Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final

choice.

choid

Suitability and durability of glove type is dependent on usage.

Body protection See Other protection below

Issue Date: 29/10/2013 Print Date: 19/04/2016

Other protection

- Overalls.
- ▶ P.V.C. apron.
- Barrier cream.

Thermal hazards

Not Available

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Liquid with a characteristic odour; partially miscible with water.		
Physical state	Liquid	Relative density (Water = 1)	0.99
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	π	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Combustible.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Partly Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Silicone fluids are stable under normal storage conditions. Hazardous polymerisation will not occur. At temperatures > 150 C, silicones can slowly react with the oxygen in air. When heated > 300 C, silicones can slowly depolymerise to volatile siloxanes whether or not air is present. Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Vapours of silicones are generally fairly well tolerated, however very high concentrations can cause death within minutes due to respiratory failure. At high temperatures, the fumes and oxidation products can be irritating and toxic and can cause depression leading to death in very high doses.		
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Silicone fluids do not have a high acute toxicity. They may have a laxative effect and produce central nervous system depression.		
Skin Contact	There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Low molecular weight silicone fluids may exhibit solvent action and may produce skin irritation. Excessive use or prolonged contact may lead to defatting, drying and irritation of sensitive skin		
Еуе	There is some evidence to suggest that this material can cause eye irritation and damage in some persons. Eye exposure to silicone fluids causes temporary irritation of the conjunctiva. Injection into the specific structures of the eye, however, causes corneal scarring, permanent eye damage, allergic reactions and cataract, and may lead to blindness.		
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.		
Dry-Treat INTENSIFIA	TOXICITY	IRRITATION	
	Not Available	Not Available	

Chemwatch: **4878-19**Version No: **4.1.1.1**

Page 5 of 6

Dry-Treat INTENSIFIA

Issue Date: **29/10/2013**Print Date: **19/04/2016**

I or	nand
LCU	Ciiu.

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Dry-Treat INTENSIFIA	No significant acute toxicological data identified in literature search.		
Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Legend:

X − Data available but does not fill the criteria for classification
 ✓ − Data required to make classification available

Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Harmful to aquatic organisms.

For Siloxanes

Environmental Fate: Siloxanes are used in cosmetics, wax, polishes, and to a minor extent in several other applications.

Atmospheric Fate: In the presence of nitrate ions, short chain siloxanes are broken down by sunlight to the level of silicate within days. The main source atmospheric siloxane release to the air is via evaporation.

Aquatic Fate: It is well accepted that polydimethylsiloxane fluids become permanent residents of sediment but should not have adverse environmental effects.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ► Reduction
- ► Reuse
- ► Recycling

 ► Disposal (if all a

Product / Packaging disposal

▶ Disposal (if all else fails)
This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ► Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

COMBUSTIBLE LIQUID	COMBUSTIBLE LIQUID, regulated for storage purposes only
Marine Pollutant	NO

Issue Date: **29/10/2013**Print Date: **19/04/2016**

HAZCHEM

Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ
Canada - NDSL	Y
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Y
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Y
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

 ${\sf PC-TWA: Permissible \ Concentration-Time \ Weighted \ Average}$

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit,

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.