

# Specifier's Guide: Natural Stone & Man-made Facade including thin stone veneer

## Seal

Fully breathable impregnating / penetrating sealers providing premium oil and water repellence. These impregnators do not form a film and do not change the natural look or texture of the surface.

Product	Protection	Low-VOC	Lifespan
<b>STAIN-PROOF™ Original</b> Permanent, invisible impregnating sealer	<ul style="list-style-type: none"> <li>Permanent water and oil-based stain repellence</li> <li>Efflorescence</li> <li>Freeze-thaw/salt spalling*</li> </ul>	No	15 Years** Warranty
<b>METACRÈME™</b> Permanent, invisible, water-based impregnating sealer	<ul style="list-style-type: none"> <li>Permanent water and oil-based stain repellence</li> <li>Efflorescence</li> <li>Freeze-thaw/salt spalling*</li> </ul>	Yes - LEED Compliant	15 Years** Warranty
<b>Stain-Repella™</b> Invisible penetrating sealer	<ul style="list-style-type: none"> <li>Water and oil-based stain repellence</li> </ul>	Yes - LEED Compliant	5-years†

\* For softer, more, porous materials use DRY-TREAT 40SK | \*\* If applied by an accredited applicator | † Depending on surface use & traffic



Unsealed

Sealed



Dry-Treat™  
STAIN-PROOF™ Original



Dry-Treat™  
METACRÈME™



Hanafinn™  
Stain-Repella™

## Enhance

Fully breathable impregnating enhancers enrich the color of natural stone and man-made materials, as well as provide premium oil and water repellence. Dry-Treat enhancers do not form a coating like traditional enhancers and do not yellow, whiten, crack or peel. After a few years when the enhancement starts to fade, simply clean and recoat, with no stripping required.

Product	Protection	Low-VOC	Lifespan
<b>INTENSIFIA™</b> Color enhancer & sealer for medium to dense surfaces	<ul style="list-style-type: none"> <li>Premium water and oil repellence</li> </ul>	Yes - LEED Compliant	5 Year Warranty**

\*\* If applied by an accredited applicator



Before

After



Dry-Treat™  
INTENSIFIA™

For coverage rates please refer to the Product Coverage Guide to calculate the amount of product required.

# Specifier's Guide: Natural Stone & Man-made Facade including thin stone veneer

## Consolidate softer, more porous materials

Fully breathable impregnating consolidator strengthens softer, highly porous materials by approximately 30 to 40% and creates a deep water repellent layer inside the material.

Product	Protection	Low-VOC	Lifespan
<b>DRY-TREAT 40SK™</b> Consolidator and freeze-thaw/salt spalling protection for softer, more porous materials	<ul style="list-style-type: none"> <li>• Freeze-thaw/salt spalling</li> <li>• Permanent water repellence</li> <li>• Strengthens treated surfaces by 30% - 40%</li> <li>• Efflorescence</li> </ul>	Yes	15-year** Warranty

\*\* If applied by an accredited applicator

**All softer, more porous materials, such as limestone, travertine and sandstone, in a coastal regions or in a freeze-thaw environment should be treated with Dry-Treat 40SK.**



Freeze-thaw spalling



DRY-TREAT 40SK™

## Clean

Powerful, safer environmentally responsible cleaners.

Product	Cleans
<b>Eff-Erayza™</b> Powerful, safer acid cleaner	<ul style="list-style-type: none"> <li>• Efflorescence</li> <li>• Rust marks</li> <li>• Grout haze</li> <li>• Limescale</li> <li>• Mortar mess</li> <li>• Fireplace soot</li> </ul>
<b>Oxy-Klenza™</b> Outdoor surface cleaner	<ul style="list-style-type: none"> <li>• Stains from oil, mold, food and beverage, and leaf marks</li> </ul>

**Note:** EFF-ERAYZA™ is acidic / corrosive and will etch and pit acid sensitive surfaces such as marble, limestone, travertine, some concrete / grout products and some metals including aluminium. Do not allow product to come in contact with any non-recommended surface.

Efflorescence removal



Before

After



HANAFINN™  
Eff-Erayza™

General cleaning



Before

After



HANAFINN™  
Oxy-Klenza™

A comprehensive surface maintenance guide is available on the Dry-Treat website: [www.drytreat.com/quickdocs.html](http://www.drytreat.com/quickdocs.html)

For coverage rates please refer to the Product Coverage Guide to calculate the amount of product required.